



WIT WATER IONIZER TECHNOLOGIES

MODEL # 4-BANK-CHROMIUM-6 REMOVAL SYSTEM

SYSTEM DIMENSIONS, SETUP & CONFIGURATION:

- 15" LENGTH x 15" HIGH x 5" WIDE
- WATER FLOW :: FLUORIDE PRE-FILTER IN – STAGE 3 OUT
- ****IMPORTANT** - FLUSH WITH 4 GALLONS OF WATER BEFORE CONNECTING TO IONIZER TO REMOVE ANY LOOSE RESIDUE OR PARTICLES FROM THE FILTERS**

*****REFER TO INSTALLATION SHEET FOR SPECIFIC INSTALLATION INSTRUCTIONS*****

PRE-FILTRATION:

FLUORIDE REMOVAL IS ACHIEVED BY UTILIZING THE ADVANCED MEDIA TECHNOLOGY OF THE FOLLOWING:

- **SIR-900:** A SYNTHETIC ALUMINUM OXIDE THAT IS PROCESSED TO HAVE MINIMUM FINES AND OTHER FOREIGN MATTER. CARTRIDGE REMOVES FLUORIDE BY A CHEMICAL REACTION WITH THE MEDIA. IT HAS MINIMAL SHRINKAGE/SWELLING AND LOW PRESSURE LOSS.

PRODUCT IS PHYSICALLY STABLE AND CAN BE USED WITH A LARGE RANGE OF PH. IT HAS MINIMAL SHRINKAGE/SWELLING AND LOW PRESSURE LOSS.

STAGE 1 & STAGE 2 FILTRATION:

- **STRONG ANION EXCHANGE RESIN:** DESIGNED FOR THE REMOVAL OF CHROMIUM6. THIS MEDIA IS A HIGH CAPACITY, SUPPLIED IN CHLORIDE OR HYDROXIDE FORM.

STAGE 3 FILTRATION:

KDF55 COMBINED WITH CATALYTIC CARBON FOR REDUCTION OF THE FOLLOWING:

- **KDF55:** REMOVES HEAVY METALS SUCH AS (LEAD, MERCURY, NICKEL), CHLORINE, ACTS AS A BACTERIA AND SCALE CONTROL MEDIA.
- **CATALYTIC CARBON:** REMOVES IRON, HYDROGEN SULFIDE, MANGANESE, CHLORAMINES.

**The replacement filter cartridges have a limited service life of approximately 6 months (700 gallons).
Change the filters every 6 months, or if you notice changes in taste, color or flow of the water being filtered.**

PRE-FILTER SYSTEM SPECIAL PRICE: \$499.95

REPLACEMENT FILTER CARTRIDGES: \$249.95